

AudioBox Series 1.2 Release Notes:

Date: May 31, 2012

- * 1818VSL Only - Remote Application now available on Apple AppStore to control 1818VSL with an iPad.
- * 1818VSL Only - All input and playback channels have now been routed to headphone by default in VSL.
- * 1818VSL Only - Firmware Updated to improve input scaling on PreAmps
- * 1818VSL Only - Output Pairs updated to so that 7/8 now shows as 1818VSL Headphone Output.
- * 1818VSL Only - Output 7/8 now shows an Headphone Icon to indicate headphone output meters.
- * 1818VSL Only - Can now monitor Main Output to SPDIF
- * 1818VSL Only - Can now send Main Mix to SPDIF input in your recording software.

- * Single Installer for AudioBox USB, AudioBox 22VSL, AudioBox 44VSL and AudioBox 1818VSL
- * Input Metering was adjusted to match Studio 1
- * Improved USB 3.0 Support
- * Resolution for VSL has been adjusted for a minimum viewing screen with 1024 x 768 resolution.
- ** PC Users - May need to hide windows Toolbar or move it to another position on the screen to access the scrollbar in VSL.
- * Improvements made to the installer and uninstaller.

- * PC Only - VSL will run on Startup by Default for windows, this is to make signal available to headphones.
VSL will run in the background even after the window is closed.
- * PC Only - Performance Mode has been removed to improve driver performance and device compatibility when running with low buffer settings.
- * PC Only - Removed Option for 32 Samples Per Buffer
- * PC Only - Operating at 44.1KHZ or 48KHZ Lowest Buffer Option is 64 Samples
- * PC Only - Operating at 88.2KHZ or 96KHZ Lowest Buffer Option is 128 Samples

Known Issues for this release

- * Generic Icons will be displayed in Studio 1 for AudioBox products on PC only with Studio 1 version 2.0.5.
This will be resolved in a future release of Studio 1.